





How to Locate and Read Rheem/Ruud/Richmond Serial Numbers

The serial number identification on all rating labels contains ten digits. It follows the example below:

<i>09</i>	<i>12</i>	<i>D</i>	<i>01234</i>
Month Manufactured	Year Manufactured	Plant Line Code	Consecutive Serial Number

Your warranty is based on the date of manufacture and the warranty code listed in the model number. To verify if your heater is in warranty call 1-800-621-5622 and listen for the prompt to take you to Warranty.





How to Locate and Read Rheem/Ruud/Richmond Serial Numbers

Effective April 2, 2012 product being produced in Mexicali started using a new rating label. Effective June 4th, product being manufactured in Nuevo Laredo started using the new rating label. You will notice a different format based on the week and year of manufacture. Please see the below key and the enclosed picture. Please note the date of Manufacture on the 3rd line.

- Serial Number
 - PWWYY00001
 - P = Plant Identification Code – see below
 - WW = week
 - YY = Year
 - PWWYY00001A
 - A, B, C, etc Suffix after serial number designates a conversion
 - Each manufacturing plant will migrate to the new serial number as they are migrated to Oracle

Plant location	Plant Identification Code
Montgomery	A
Water Heater Innovations	W (Marathon and Eclipse)
Nuevo Laredo	Q
Mexicali	M
Canada	C




For Example the serial number:

M141209135

Mexicali plant, week 14, 2012, (09135) actual consecutive serial number.

Q231299996

Nuevo Laredo plant, week 23, 2012, (99996) actual consecutive serial number.

Rheem Fury 6YR		Manufacturer's Rating Label
SERIAL NO. RHLN0231299996	MFG. DATE: 30MAY2012	 
MODEL NO. 42V50SF	Cap. U.S. Gals. 50	
Input BTUH 40,000	TYPE GAS – NATURAL	
Gas PRESS. IN. W.C. – Manifold – 4.0	Max. Inlet – 10.5 Min. Inlet – 5.0	
ANS Z21.10.1a•CSA 4.1a-2009		
COMPLIES WITH JURISDICTIONS HAVING 40ng/J NOx REGULATIONS		
MINIMUM CLEARANCES FROM COMBUSTIBLES 1" Sides and 0" rear in a closet – 0" Sides and rear in an alcove. 3" front of control (or control box) to closet door 12" from top pan to ceiling May be installed in an alcove or closet and on combustible flooring.	CERTIFIED FOR INSTALLATIONS UP TO 5999 FT. ALTITUDE	
	MAX WORKING PRESSURE 150 PSI	
Rheem Manufacturing Co. Water Heating Division Montgomery, Alabama 36117 USA		