



# SALES FACT SHEET



Featuring  
New Industry Standard  
R-410A Refrigerant

**R-410A**



"Visit [www.Rheem.com](http://www.Rheem.com)  
for complete details."



## 15PJL SERIES

### GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable periods stated, in accordance with the terms of the limited warranty.

|  |                     |
|--|---------------------|
| Conditional Parts Warranty*<br>(Registration Required) | .....Ten (10) Years |
| Conditional Compressor*<br>(Registration Required)     | .....Ten (10) Years |
| Limited Parts  | .....Five (5) Years |

\*See Product Warranty Card for Details.

|           |                 |                          |                         |  |                       |                    |
|-----------|-----------------|--------------------------|-------------------------|--|-----------------------|--------------------|
| <b>15</b> | <b>P</b>        | <b>J</b>                 | <b>L</b>                | <b>18</b>  | <b>A</b>              | <b>01</b>          |
| 15 SEER   | P = HEAT PUMP   | VOLTAGE                  | DESIGN SERIES           | NOMINAL COOLING CAPACITY   | CABINET               | RHEEM VALUE SERIES |
|           |                 | J = 208-230 SINGLE PHASE | L = 1ST DESIGN (R-410A) | 18 = 18,000 BTU/HR [5.28 kW]<br>24 = 24,000 BTU/HR [7.03 kW]<br>30 = 30,000 BTU/HR [8.79 kW]<br>36 = 36,000 BTU/HR [10.55 kW]<br>42 = 42,000 BTU/HR [12.31 kW]<br>48 = 48,000 BTU/HR [14.07 kW]<br>60 = 60,000 BTU/HR [17.58 kW] | A = FULL METAL JACKET |                    |
| Price     | Starting at: \$ |                          |                         |  |                       |                    |

### Features

- 35" Maximum Unit Height.
- Coils constructed with copper tubing and enhanced aluminum fins.
- Strong, attractive cabinet—louvered design protects the coil from damage.
- Expansion Valves with Internal Check Valve—Provides for quieter refrigerant metering.
- Enhanced Demand Defrost Control
- Factory Installed Low Pressure Control
- Non-Cycling Reversing Valve
- Hot Gas Muffler
- Service Valves
- Grille/motor mount for quiet fan operation.
- Easily accessible control box.
- Bi-Directional Filter Drier (Field Installed)
- Certified and rated under A.H.R.I. Standard 240.
- U.L listed.

### Accessories/Options

- Optional High Pressure Control (Model No. RXAB-A07)
- Heat Pump Thermostat Warning Light Kit (Model No. RXPX-D01)
- Low Ambient Control (Model No. RXAD-A08)
- Outdoor Thermostats (Model No. RXPT-A01, A02, A03 or A04)
- Heat Pump Monitor (Model No. RXPM-B01)
- Thermostats and Subbases (Available through the PROSTOCK® department)
- Compressor Time Delay Control (Model No. RXMD-B01)
- Blower Time Delay Control (Model No. RXMD-C04) RXMD-C04 is not required if the outdoor unit is matched with a Rheem Value Series furnace or air handler, or if the furnace or air handler used has a blower off time delay built-in.
- Sound Enclosure\*
- Start Components\*

\*Available through the PROSTOCK® department.



(IN CERTAIN MATCHED SYSTEMS)

