The new degree of comfort.™

Fury® gas water heaters feature the Guardian System – engineered to exceed ANSI standards for flammable vapor ignition resistance

Efficiency

- 0.58 - 0.61 EF
- More hot water at a low operating cost

Performance

- FHR: 49 to 88 gallons for natural gas
- Recovery: 25.5 to 38.2 gallons at a 90 degree rise, based on model

Guardian System™ & Sensor

- Exclusive air/fuel shut-off device
- Maintenance free – no filter to clean

Longer Life

- Patented magnesium anode rod with resistor protects the tank from rust

High Altitude Compliant

- All models certified up to 6,000 ft. above sea level

Plus…

- Easy to light – no matches required
- EverKleen™ patented system fights sediment build-up
- Standard replacement parts

Warranty

- 6-Year limited tank and 1-year limited parts warranty*

*See Residential Warranty Certificate for complete information



Fury

30, 40 and 50-Gallon Capacities
Up to 45,000 Btu/h
Natural and LP Gas

*LEED Point = 1

DESCRIPTION	FEATURES			ROUGHING IN DIMENSIONS (SHOWN IN INCHES)									ENERGY INFO.
MODEL NUMBER	GAS INPUT IN THOUS. BTU/H NAT.	RECOVERY IN G.P.H. 90° RISE NAT.	FIRST HOUR DEL. G.P.H. NAT.	HT. TO VENT A	TANK HT. B	DIAM. C	HT. TO GAS CONN. D	VENT SIZE E	WATER CONN. CNTR. F	HT. TO SIDE T&P G	WATER CONN. H	SHIP. WT. (LBS)	ENERGY FACTOR NAT.
RR30-30FV	30	25.5	49	49-3/4	46-1/4	19-3/4	14-1/2	3	8	40-1/4	3/4	98	0.61
RR40-36FV1	36	30.5	72	53-1/8	49-3/8	20-1/4	14-1/2	3-4*	8	42-3/4	3/4	130	0.59
RR50-45FV1	45	38.2	88	54-3/8	52-1/2	22-1/4	14-1/2	4	8	44	3/4	160	0.58

Specify LP gas when ordering. Add "P" suffix to the model number. Example: RR30-30PFV.

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

Rheem Water Heating • 101 Bell Road
Montgomery, Alabama 36117-4305 • www.rheem.com

Rheem Canada Ltd./Ltée • 125 Edgeware Road, Unit 1
Brampton, Ontario L6Y 0P5 • www.rheem.com

08/12 WP FORM NO. 101-6CAN Rev. 14