SALES FACT SHEET

RGRA-/RGRB- SERIES
Up to 93.5% A.F.U.E.†
Input Rates 45 to 120 kBTU
[13.19 to 35.17 kW]

Rheem *Classic® Series*
Upflow Gas Furnaces

Features

- The Rheem High Efficiency line of upflow gas furnaces are designed for utility rooms, closets or alcoves.
- The design is certified by CSA.
- Heat exchanger is constructed of aluminized steel for maximum corrosion resistance and thermal fatigue reliability.
- Low profile "34 inch" design is lighter and easier to handle and leaves room for optional accessories.
- Left or right side gas, electric, and condensate drainage connections on upflow models.
- Integrated control board manages all operational functions and provides hookups for humidifier and electronic air cleaner.
- An insulated blower compartment, a slow-opening gas valve and a specially designed inducer system make it one of the quietest furnaces on the market today.
- Pre-paint galvanized steel cabinet.
- Molded permanent filters.
- Optional indoor or outdoor combustion air. In addition, combustion air may be piped to either the top or side of the cabinet on all upflow models. A special molded fitting is provided to ease installation.
- Transformer and control fuse protection.
- Solid bottom is standard.
- Control board diagnostics.
- A variety of cooling coils and plenums designed to use with the Classic® gas furnaces are available as optional accessories for air conditioning models.

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Heat Exchanger . . . . . .Limited Lifetime
Conditional Parts
(Registration Required) . . . . . .Ten (10) Years
Conditional Unit Replacement
(Registration Required) . . . . . .Ten (10) Years

†A.F.U.E. (Annual Fuel Utilization Efficiency) calculated in accordance with Department of Energy test procedures.

MODEL	INPUT-BTU/HR [kW] ①	HEATING CAPACITY BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
RGRA-04EMAES	45,000 [13.19]	42,000 [12.31]	885 [417]	1195 [564]	111 [50.3]	
RGRA-06EMAES	60,000 [17.58]	56,000 [16.41]	845 [398]	1100 [519]	117 [53.1]	
RGRB-07EMAES	75,000 [21.98]	70,000 [20.51]	1050 [495]	1110 [524]	124 [56.2]	
RGRB-07EYBGS	75,000 [21.98]	70,000 [20.51]	1275 [600]	1540 [725]	137 [62.1]	
RGRA-09EZAJS	90,000 [26.38]	84,000 [24.62]	1465 [691]	1910 [901]	148 [67.1]	
RGRA-10EZAJS	105,000 [30.77]	97,000 [28.43]	1445 [682]	1810 [854]	152 [68.9]	
RGRA-12ERAJS	120,000 [35.17]	113,000 [33.12]	1580 [745]	1900 [897]	160 [72.6]	

① See Conversion Kit Index Form for high altitude derate.

[ ] Designates Metric Conversions

Accredited by the RvA
ISO 9001:2008
Certificate Number: 30164

Rheem Heating, Cooling and Water Heating
P.O. Box 17010, Fort Smith, AR 72917

FORM NO. G11-532-SFS
PRINTED IN U.S.A. QG 11-12

SALES FACT SHEET

RGRA-/RGRB- ACCESSORIES

Description	Part No.	Price
Condensate Pump Kit	RXGY-B01	
External Bottom Filter Rack 15 3/4" x 25 (Use filter shipped with furnace or a suitable 1" filter)	RXGF-CB	
External Side Filter Rack (Use filter shipped with furnace or a suitable 1" filter)	RXGF-CA	
Fossil Fuel Kit	RXPF-F02	
High Altitude Conversion Kit (Input: 105,000 BTUH)	RXGY-F34	
High Altitude Conversion Kit (Input: 120,000 BTUH)	RXGY-F35	
High Altitude Conversion Kit (Input: 60,000 BTUH)	RXGY-F36	
High Altitude Conversion Kit (Input: 75,000 BTUH)	RXGY-F37	
High Altitude Conversion Kit (Input: 90,000 BTUH)	RXGY-F37	
Horizontal Two Pipe Kit (Canadian Installations)	RXGY-D02A	
Horizontal Two Pipe Kit (Canadian Installations)	RXGY-D03A	
Horizontal Two Pipe Kit (Canadian Installations)	RXGY-D04A	
Horizontal Two Pipe Kit (US Installations)	RXGY-D02	
Horizontal Two Pipe Kit (US Installations)	RXGY-D03	
Horizontal Two Pipe Kit (US Installations)	RXGY-D04	
Horizontal Two Pipe Kit (US Installations)	RXGY-G02	
LP Kit - HA & HH Fuel Codes Only (US & Canadian)	RXGY-FP27	
LP Kit-HG & HB Fuel Codes Only (US & Canadian)	RXGY-FP07	
Neutralizer Kit	RXGY-A01	
Return Air Plenum	RXGR-C17B	
Return Air Plenum	RXGR-C21B	
Return Air Plenum	RXGR-B24B	
Vent Termination Kit - Concentric Horizontal/Vertical (US & Canadian Installations)	RXGY-E03A	
Plenum Adapter for "A-Coil" Plenum RXAL-B16BU (Furnace Width 17 1/2", Plenum Width 16 1/4")	RXAA-C185	
Plenum Adapter for "A-Coil" Plenum RXAL-B20BU (Furnace Width 17 1/2", Plenum Width 20 1/4")	RXAA-C173	
Plenum Adapter for "A-Coil" Plenum RXAL-B21BU (Furnace Width 17 1/2", Plenum Width 21 5/8")	RXAA-C187	
Plenum Adapter for "A-Coil" Plenum RXAL-B25BU (Furnace Width 17 1/2", Plenum Width 25 1/4")	RXAA-C174	
Plenum Adapter for "A-Coil" Plenum RXAL-B25BU (Furnace Width 21", Plenum Width 25 1/4")	RXAA-C175	
Plenum Adapter for "A-Coil" Plenum RXAL-B22BU (Furnace Width 21", Plenum Width 22 1/4")	RXAA-C176	
Plenum Adapter for "A-Coil" Plenum RXAL-B21BU (Furnace Width 21", Plenum Width 21 5/8)	RXAA-C188	
Plenum Adapter for "A-Coil" Plenum RXAL-B25BU (Furnace Width 24 1/2", Plenum Width 25 1/4")	RXAA-C177	
Plenum Adapter for "A-Coil" Plenum RXAL-B21BU (Furnace Width 24 1/2", Plenum Width 25 5/8")	RXAA-C187	
Gas Orifice (Qty 1) Size 39	62-22175-39	
Gas Orifice (Qty 1) Size 40	62-22175-40	
Gas Orifice (Qty 1) Size 41	62-22175-41	
Gas Orifice (Qty 1) Size 42	62-22175-42	
Gas Orifice (Qty 1) Size 43	62-22175-43	
Gas Orifice (Qty 1) Size 44	62-22175-44	
Gas Orifice (Qty 1) Size 45	62-22175-45	
Gas Orifice (Qty 1) Size 46	62-22175-46	
Gas Orifice (Qty 1) Size 47	62-22175-47	
Gas Orifice (Qty 1) Size 48	62-22175-48	
Gas Orifice (Qty 1) Size 49	62-22175-49	
Gas Orifice (Qty 1) Size 50	62-22175-50	
Gas Orifice (Qty 1) Size 51	62-22175-51	
Gas Orifice (Qty 1) Size 52	62-22175-52	
Gas Orifice (Qty 1) Size 53	62-22175-53	
Gas Orifice (Qty 1) Size 54	62-22175-54	
Gas Orifice (Qty 1) Size 55	62-22175-55	
Gas Orifice (Qty 1) Size 56	62-22175-56	
Gas Orifice (Qty 1) Size 57	62-22175-57	
Gas Orifice (Qty 1) Size 58	62-22175-58	
Gas Orifice (Qty 1) Size 59	62-22175-59	
Gas Orifice (Qty 1) Size 60	62-22175-60	
Gas Orifice (Qty 1) Size 61	62-22175-61	
Gas Orifice (Qty 1) Size 62	62-22175-62	
Gas Orifice (Qty 1) Size 63	62-22175-63	
Gas Orifice (Qty 1) Size 64	62-22175-64	
Gas Orifice (Qty 1) Size 1.10mm	62-22172-90	
Gas Orifice (Qty 1) Size 1.15mm	62-22175-91	