SALES FACT SHEET

RGTC- SERIES
Up to 95% A.F.U.E.†
Models with Input Rates of 45, 60, 75, 90 & 105 kBTU [13.19, 17.58, 22, 26.38 & 30.77 kW]

Rheem *Classic*® *Series* Downflow/Horizontal Gas Furnaces

Features

- Heat exchanger is constructed of all stainless steel for maximum corrosion resistance and thermal fatigue reliability.
- Low profile "34 inch" design is lighter and easier to handle and leaves room for optional accessories.
- Top electrical connections, left or right gas and condensate drainage connections on downflow models.
- Condensate drain for horizontal application provided standard.
- Integrated control board manages all operational functions and provides hookups for humidifier and electronic air cleaner.
- An insulated blower compartment, a slow-opening gas valve and a specially designed inducer system make it one of the quietest furnaces on the market today.
- Pre-paint galvanized steel cabinet.
- Molded permanent filters.
- Optional indoor or outdoor combustion air.
- Transformer and control fuse protection.
- Control board diagnostics.

A variety of cooling coils and plenums designed to use with the Classic® 90 Plus gas furnaces are available as optional accessories for air conditioning models.

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Heat Exchanger . . . . . .Limited Lifetime

Conditional Parts
(Registration Required) . . . . . .Ten (10) Years

†A.F.U.E. (Annual Fuel Utilization Efficiency) calculated in accordance with Department of Energy test procedures.

MODEL	INPUT-BTU/HR [kW] ①	HEATING CAPACITY BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.12 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
RGTC-04EMAES	45,000 [13.19]	43,000 [12.61]	866 [409]	1220 [576]	123 [56]	
RGTC-06EMAES	60,000 [17.58]	58,000 [16.99]	1122 [530]	1242 [586]	126 [57]	
RGTC-07ERBGS	75,000 [21.98]	72,500 [21.25]	1516 [716]	1559 [736]	137 [62]	
RGTC-09EZAJS	90,000 [26.38]	87,000 [25.50]	1698 [802]	1850 [873]	148 [67]	
RGTC-10ERBJS	105,000 [30.77]	101,500 [29.75]	1812 [856]	1977 [934]	160 [73]	

① See Conversion Kit Index Form for high altitude derate.

[ ] Designates Metric Conversions

Accredited by the RvA
ABS Quality Evaluations, Inc. Management System Certification
ANAB ACCREDITED
ISO 9001:2008
Certificate Number: 30164

DESIGN CERTIFIED

CERTIFIED

AHRI CERTIFIED™ www.ahridirectory.org

Rheem Heating, Cooling and Water Heating
P.O. Box 17010, Fort Smith, AR 72917

FORM NO. G11-526-SFS
PRINTED IN U.S.A. QG 7-12

SALES FACT SHEET

RGTC ACCESSORIES

Description	Part No.	Price
Condensate Pump Kit	RXGY-B01	
External Bottom Filter Rack 15 3/4" x 25 (Use filter shipped with furnace or a suitable 1" filter)	RXGF-CB	
External Side Filter Rack (Use filter shipped with furnace or a suitable 1" filter)	RXGF-CA	
Fossil Fuel Kit	RXPF-F02	
High Altitude Conversion Kit (Input: 105,000 BTUH)	RXGY-F34	
High Altitude Conversion Kit (Input: 120,000 BTUH)	RXGY-F35	
High Altitude Conversion Kit (Input: 60,000 BTUH)	RXGY-F36	
High Altitude Conversion Kit (Input: 75,000 BTUH)	RXGY-F37	
High Altitude Conversion Kit (Input: 90,000 BTUH)	RXGY-F37	
Horizontal Two Pipe Kit (Canadian Installations)	RXGY-D02A	
Horizontal Two Pipe Kit (Canadian Installations)	RXGY-D03A	
Horizontal Two Pipe Kit (Canadian Installations)	RXGY-D04A	
Horizontal Two Pipe Kit (US Installations)	RXGY-D02	
Horizontal Two Pipe Kit (US Installations)	RXGY-D03	
Horizontal Two Pipe Kit (US Installations)	RXGY-D04	
Horizontal Two Pipe Kit (US Installations)	RXGY-G02	
LP Kit - HA & HH Fuel Codes Only (US & Canadian)	RXGY-FP27	
LP Kit-HG & HB Fuel Codes Only (US & Canadian)	RXGY-FP07	
Neutralizer Kit	RXGY-A01	
Return Air Plenum	RXGR-C17B	
Return Air Plenum	RXGR-C21B	
Return Air Plenum	RXGR-B24B	
Vent Termination Kit - Concentric Horizontal/Vertical (US & Canadian Installations)	RXGY-E03A	
Plenum Adapter for "A-Coil" Plenum RXAL-B16BU (Furnace Width 17 1/2", Plenum Width 16 1/4")	RXAA-C185	
Plenum Adapter for "A-Coil" Plenum RXAL-B20BU (Furnace Width 17 1/2", Plenum Width 20 1/4")	RXAA-C173	
Plenum Adapter for "A-Coil" Plenum RXAL-B21BU (Furnace Width 17 1/2", Plenum Width 21 5/8")	RXAA-C187	
Plenum Adapter for "A-Coil" Plenum RXAL-B25BU (Furnace Width 17 1/2", Plenum Width 25 1/4")	RXAA-C174	
Plenum Adapter for "A-Coil" Plenum RXAL-B25BU (Furnace Width 21", Plenum Width 25 1/4")	RXAA-C175	
Plenum Adapter for "A-Coil" Plenum RXAL-B22BU (Furnace Width 21", Plenum Width 22 1/4")	RXAA-C176	
Plenum Adapter for "A-Coil" Plenum RXAL-B21BU (Furnace Width 21", Plenum Width 21 5/8)	RXAA-C188	
Plenum Adapter for "A-Coil" Plenum RXAL-B25BU (Furnace Width 24 1/2", Plenum Width 25 1/4")	RXAA-C177	
Plenum Adapter for "A-Coil" Plenum RXAL-B21BU (Furnace Width 24 1/2", Plenum Width 25 5/8")	RXAA-C187	
Gas Orifice (Qty 1) Size 39	62-22175-39	
Gas Orifice (Qty 1) Size 40	62-22175-40	
Gas Orifice (Qty 1) Size 41	62-22175-41	
Gas Orifice (Qty 1) Size 42	62-22175-42	
Gas Orifice (Qty 1) Size 43	62-22175-43	
Gas Orifice (Qty 1) Size 44	62-22175-44	
Gas Orifice (Qty 1) Size 45	62-22175-45	
Gas Orifice (Qty 1) Size 46	62-22175-46	
Gas Orifice (Qty 1) Size 47	62-22175-47	
Gas Orifice (Qty 1) Size 48	62-22175-48	
Gas Orifice (Qty 1) Size 49	62-22175-49	
Gas Orifice (Qty 1) Size 50	62-22175-50	
Gas Orifice (Qty 1) Size 51	62-22175-51	
Gas Orifice (Qty 1) Size 52	62-22175-52	
Gas Orifice (Qty 1) Size 53	62-22175-53	
Gas Orifice (Qty 1) Size 54	62-22175-54	
Gas Orifice (Qty 1) Size 55	62-22175-55	
Gas Orifice (Qty 1) Size 56	62-22175-56	
Gas Orifice (Qty 1) Size 57	62-22175-57	
Gas Orifice (Qty 1) Size 58	62-22175-58	
Gas Orifice (Qty 1) Size 59	62-22175-59	
Gas Orifice (Qty 1) Size 60	62-22175-60	
Gas Orifice (Qty 1) Size 61	62-22175-61	
Gas Orifice (Qty 1) Size 62	62-22175-62	
Gas Orifice (Qty 1) Size 63	62-22175-63	
Gas Orifice (Qty 1) Size 64	62-22175-64	
Gas Orifice (Qty 1) Size 1.10mm	62-22172-90	
Gas Orifice (Qty 1) Size 1.15mm	62-22175-91	